

The same SE control drives six different Fleck valves, saving time in installation, service, and training.



5600SE



ProFloSE



TwinFloSE



2510SE



2750SE



9000SE

SE Valve Specifications

Valve	Valve Body	Inlet/Outlet	Service Flow Rate (gpm)*	Backwash Flow Rate (gpm)**	Meter
5600SE	Noryl®	3/4" or 1"	20	7	Turbine
ProFloSE	Noryl®	3/4" or 1"	21	17	Turbine
TwinFloSE	Noryl®	3/4" or 1"	15	4	Turbine
2510SE	Noryl®	3/4" or 1"	19	17	Turbine
2750SE	Brass	1"	26	25	Impeller
9000SE	Brass	3/4" or 1"	21	8.5	Impeller

* 15 psi drop ** 25 psi drop

Noryl® is a registered trademark of General Electric Corporation.

The 5600SE 24 volt/60 Hertz powerhead is recognized by Underwriters Laboratories Inc.

Representative samples of this component have been evaluated by UL and meet the applicable requirements.

INTRODUCING THE FLECK SE LINE OF CONTROL VALVES

The end of complicated electronics



Six great valves, one simple control



Fleck Controls, Inc.
20580 Enterprise Avenue • Brookfield, WI 53008
Phone: (262) 784-4490 • Fax: (262) 784-7794
www.pentairwater.com
www.fleckcontrols.com



©2001 Fleck Controls, Inc. MK 5M 6/01
Part No. 40620



Fleck SE Control Valves

Because the best performance doesn't have to be complicated



Performance People Trust™

Simple Electronics from Fleck provide easy, step-by-step programming at the touch of a button.

The same SE control drives six different Fleck valves, saving you time in installation, service, and training. Unlike other electronic valves, the SE control performs without switching out cams or fumbling with jumpers, pins, and cryptic calculations.

A bright LED displays the time of day, soft water remaining, and self diagnostic

Every Fleck valve is backed with a Five-Year Warranty!

indicator so you're never left in the dark. Fleck valves with SE controls, simply the best solution for all of your residential water treatment applications.



Bright Red LED Display














- True Time of Day in Hours and Minutes
- Volume of Soft Water Remaining
- Regeneration Steps and Cycle Time Remaining
- Service and Self Diagnostic Indicators

Easy, Friendly Programming

- Quick and Easy Setup of Capacity, Regeneration Time, and Day Override
- Advanced Programming Options including up to Six Independently Adjustable Cycle Times
- Program Memory stores Timer Settings without Batteries
- Electronic Step-by-Step Regeneration
- Regeneration Tonight and Regenerate Now Option



Setup in Five Simple Steps

1. To set the **Time of Day**, simply push the up  or down  buttons.
2. **Get into the Programming Mode** by pressing the up and down buttons   together for five seconds.
3. Now, **set the Capacity** by pushing the up  or down  buttons. To continue, push the Extra Cycle button .
4. Next, **set the Regeneration Time** by pushing the up  or down  buttons. To continue, push the Extra Cycle button .
5. Finally, **set the Regeneration Day Override** by pushing the up  or down  buttons. To end the Programming Mode, push the Extra Cycle button .

Unique to Fleck... our SE valves undergo rigorous fatigue testing, passing 250,000 pressure cycles up to 190 psi and 10,000 complete regeneration cycles. That equals 27 years of uninterrupted daily use!